DATASHEET - 10731450



Fuse-link, LV, 40 A, AC 500 V, 14 x 51 mm, gL/gG, IEC

EL Number (Norway) **C14G40 1600241**

General specifications			
Product name			Eaton Bussmann series low voltage cylindrical fuse
Part no.			C14G40
EAN			5027590494076
Product Length/Depth			51 millimetre
Product height			14.3 millimetre
Product width			14.3 millimetre
Product weight			20.5 gram
Compliances			RoHS Compliant CE Marked GoST-R
Certifications			IEC 60269
Product Tradename			None
Product Type			Low voltage cylindrical fuse
Product Sub Type			None
Electrical data			
Amperage Rating			40 A
Voltage rating			500 V
Voltage type			AC
Breaking capacity			120 kA
Utilization category			gG (cable protection/equipment protection)
Compatible fuse holder			
Suitable for			CH14 Modular fuse holder

Technical data ETIM 9.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)

Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss13-27-14-20-02 [AFZ797018])

Model			Ceramic fuse
Size			14x51 mm
Voltage type			AC
Rated current		A	40
Rated voltage		V	500
Utilization category			gG (cable protection/equipment protection)
Rated operating frequency		Hz	45 - 62
Type of fuse status indicator			Other
Release characteristic			Other
Breaking capacity		kA	120
Power loss at rated current		W	4.75

© 04/2023 by Eaton Industries GmbH