DATASHEET - 10725931



Fuse, 2A, AC 550 V, V88/F1, 14 x 59 mm, gL/gG

NSD2

General specifications

Product name	Eaton Bussmann series low voltage british standard fuse
Part no.	NSD2
EAN	5027590504805
Product Length/Depth	60 millimetre
Product height	14 millimetre
Product width	14 millimetre
Product weight	16.2 gram
Compliances	RoHS Compliant CE Marked
Certifications	BS88 IEC 60269-2
Product Tradename	None
Product Type	Low voltage british standard fuse
Product Sub Type	None

Electrical data

Amperage Rating	2 A
Voltage rating	550 V
Voltage type	AC
Breaking capacity	80 kA
Class	Class gG/gL

Product specifications

Application	general industrial applications
Fuse type	NSD
Fuse size	BS88/F1
Fitted with:	Offset bladed tags
Connection	Blade end
Quantity	20

Compatible fuse holder

Suitable for	SC32 Safeclip fuse holder 32NNS Safeloc fuse holder

Technical data ETIM 9.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)

Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss13-27-14-20-90 [BAB264016])

Fuse system according to IEC 60269		Fuse system E
Fuse construction type according to IEC 60269		F1
Type of current		AC
Rated voltage AC	V	550
Rated voltage DC	V	
Rated current	A	2
Utilization category		gG (cable protection/equipment protection)
Breaking capacity	kA	80
Colour code		None
Type of fuse status indicator		None
Power loss at rated current	W	0.9
Mounting holes		
Centre-to-centre distance of connections	mm	

© 04/2023 by Eaton Industries GmbH