DATASHEET - 10721570



Fuse, 32A, AC 550 V, V88/F1, 14 x 59 mm, gL/gG

NSD32

General specifications			
Product name			Eaton Bussmann series low voltage british standard fuse
Part no.			NSD32
EAN			5027590504881
Product Length/Depth			59 millimetre
Product height			14 millimetre
Product width			14 millimetre
Product weight			15.8 gram
Compliances			CE Marked RoHS Compliant
Certifications			IEC 60269-2 BS88
Product Tradename			None
Product Type			Low voltage british standard fuse
Product Sub Type			None
Electrical data			
Amperage Rating			32 A
Voltage rating			550 V
Voltage type			AC
Breaking capacity			80 kA
Class			Class gG/gL
Product specifications			
Application			general industrial applications
Fuse type			NSD
Fuse size			BS88/F1
Fitted with:			Offset bladed tags
Connection			Blade end
Compatible fuse holder			
Suitable for			SC32 Safeclip fuse holder 32NNS Safeloc fuse holder

Technical data ETIM 9.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)

Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss13-27-14-20-90 [BAB264016])

Fuse system according to IEC 60269		Fuse system E
Fuse construction type according to IEC 60269		F1
Type of current		AC
Rated voltage AC	V	550
Rated voltage DC	V	
Rated current	A	32
Utilization category		gG (cable protection/equipment protection)
Breaking capacity	kA	80
Colour code		None
Type of fuse status indicator		None
Power loss at rated current	W	2.9
Mounting holes		
Centre-to-centre distance of connections	mm	

© 04/2023 by Eaton Industries GmbH