# DATASHEET - 10733737



**Fuse, 4A, AC 550 V, V88/F1, 14 x 59 mm, gL/gG**

**NSD4**

## General specifications

| | | |
|---|---|---|
| Product name | | Eaton Bussmann series low voltage british standard fuse |
| Part no. | | NSD4 |
| EAN | | 5027590504935 |
| Product Length/Depth | | 58.5 millimetre |
| Product height | | 13.8 millimetre |
| Product width | | 13.8 millimetre |
| Product weight | | 16.15 gram |
| Compliances | | RoHS Compliant |
| Product Tradename | | None |
| Product Type | | Low voltage british standard fuse |
| Product Sub Type | | None |

## Electrical data

| | | |
|---|---|---|
| Amperage Rating | | 4 A |
| Voltage rating | | 550 V |
| Voltage type | | AC |
| Breaking capacity | | 80 kA |
| Class | | Class gG/gL |

## Product specifications

| | | |
|---|---|---|
| Application | | general industrial applications |
| Fuse type | | NSD |
| Fuse size | | BS88/F1 |
| Fitted with: | | Offset bladed tags |
| Connection | | Blade end |
| Quantity | | 20 |

## Compatible fuse holder

| | | |
|---|---|---|
| Suitable for | | SC32 Safeclip fuse holder<br>32NNS Safeloc fuse holder |

## Technical data ETIM 9.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)

Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss13-27-14-20-90 [BAB264016])

| | | |
|---|---|---|
| Fuse system according to IEC 60269 | | Fuse system E |
| Fuse construction type according to IEC 60269 | | F1 |
| Type of current | | AC |
| Rated voltage AC | V | 550 |
| Rated voltage DC | V | |
| Rated current | A | 4 |
| Utilization category | | gG (cable protection/equipment protection) |
| Breaking capacity | kA | 80 |
| Colour code | | None |
| Type of fuse status indicator | | None |
| Power loss at rated current | W | 1.4 |
| Mounting holes | | |
| Centre-to-centre distance of connections | mm | |


© 04/2023 by Eaton Industries GmbH