DATASHEET - 10720730



Fuse-link, high speed, 20 A, DC 1000 V, IEC60269-6 type A, 10 x 38 mm, gPV, UL PV, UL, IEC

PV-20A10F

EL Number (Norway) **1600126**

General specifications

Product name	Eaton Bussmann series photovoltaic fuses
Part no.	PV-20A10F
EAN	5027590505802
Product Length/Depth	38 millimetre
Product height	10 millimetre
Product width	10 millimetre
Product weight	9.7 gram
Compliances	RoHS Compliant CE Marked
Certifications	CCC Marked UL Listed CSA Certified IEC Rated UL Listed Class NKCR2
Product Tradename	None
Product Type	High speed photovoltaic fuse
Product Sub Type	None

Electrical data

Amperage Rating	20 A
Voltage rating	1000 Vdc
Interrupt rating	50 kAIC
Class	Class gPV

Product specifications

Application	Combiner boxes, inverters, pv wire harnesses, Photovoltaic strings
Fuse type	PV-A10F
Fuse indicator	Other
Fuse size	10 x 38 mm
Quantity	10

Compatible fuse holders

Suitable for	HPV-DV Inline holder CHPV Modular fuse holder

Technical data ETIM 9.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)

Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss13-27-14-20-02 [AFZ797018])

Model		Ceramic fuse
Size		10x38 mm
Voltage type		DC
Rated current	A	20
Rated voltage	V	1000
Utilization category		gPV (photovoltaic protection)
Rated operating frequency	Hz	0 - 0
Type of fuse status indicator		Other
Release characteristic		Other
Breaking capacity	kA	50
Power loss at rated current	W	2.1

© 04/2023 by Eaton Industries GmbH