DATASHEET - 10731443



Fuse-link, high speed, 400 A, DC 1500 V, 3L, 75 x 91 x 205 mm, gPV, UL, IEC, with indicator, bolted connections

PV-400A-3L-B-15

General specifications			
Product name			Eaton Bussmann series photovoltaic fuses
Part no.			PV-400A-3L-B-15
EAN			5996516001479
Product Length/Depth			91 millimetre
Product height			91 millimetre
Product width			201.4 millimetre
Product weight			1614 gram
Compliances			CE Marked RoHS Compliant
Certifications			CSA Certified IEC 60269 UL Listed
Product Tradename			None
Product Type			High speed photovoltaic fuse
Product Sub Type			None
Electrical data			
Amperage Rating			400 A
Voltage rating			1500 Vdc
Interrupt rating			100 kAIC
Class			Class gPV
Product specifications			
Application			Photovoltaic array combiners and disconnects
Fuse type			PV-3L-B-15
Fuse indicator			Centre fuse status indicator
Fuse size			3L

Technical data ETIM 9.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss13-27-14-20-90 [BAB264016])			
Fuse system according to IEC 60269			Other
Fuse construction type according to IEC 60269			3L
Type of current			DC
Rated voltage AC		V	
Rated voltage DC		V	1500
Rated current		A	400
Utilization category			gPV (photovoltaic protection)
Breaking capacity		kA	100
Colour code			White
Type of fuse status indicator			Centre fuse status indicator
Power loss at rated current		W	61
Mounting holes			M10
Centre-to-centre distance of connections		mm	171

© 04/2023 by Eaton Industries GmbH