Product Center



INQUIRY
400-800-9662

Parameter Feature Outline Curve

Table 7 (cont.)

Cat. No.	Models MIRO	Cross-reference	Rated voltage (V)	Rated current (A)	Dimensions/sizes (mm) Fig.	A	C	D	H	md	Weight (g)
0740	RS550	-	2000	550	7.10	130	136	73	73	12	1960
0741	NGT3M	-	380/660/1000	355~630	7.10	67	76	67	85	12	910
0742	RS77	A1-66C-TS	660	200~400	7.10	42	51	50	68	8	354
0743	RS77A	A0-66C-TS	660	80~160	7.10	42	51	40	58	8	225
0744	RS77B	A2-66C-TS	660	400~630	7.10	42	51	60	78	10	518
0745	RS77C	A3-66C-TS	660	630~1000	7.10	45	54	74	92	12	865
0746	RS77H	-	1000	200~400	7.10	66	76	50	68	8	528
0747	RS78	3NE43..6B	660	315~500	7.10	66	77	60	77	10	660
0748	RS79	-	1000	400~1000	7.10	92	106	74	92	12	1655
0749	RS79A	170M34..	660	200~400	7.10	46	52	43	61	8	277
0750	RS79C	-	1000	400~1000	7.10	77	85	74	92	12	1325
0751	RS79D	140M63..	1000	800~1000	7.10	67	75	74	92	12	
0752	RS79E	170M64..	1000	630~1000	7.10	87	95	74	92	12	
0753	RS550Z	-	2000	550	7.10	135	143	74	92	12	
0754	RS82	CS5F	500	75~200	7.10	40	47	47	70	8	
0755	RS83	CS5F	500	200~400	7.10	43	51	57	82	8	
0756	RS84	CS5F	500	450~630	7.10	42	53	72	92	10	
0757	RS85	CS10F	500	200~630	7.10	66	76	60	77	10	
0758	RS86	3NE64..	500	300~700	7.10	66	77	72	92	10	
0759	RS86A(Z)	RSF-4	500/800	800~1250	7.10	68	78	85	130	12	
0760	RS87	RSF-5	500/1000	1250~1600	7.10	70	80	105	150	16	1320
0761	RS87A(Z)	RSF-6	800/1000	1600~2000	7.10	81	91	120	165	16	2216

Development
Organization
President address
Enterprise video
Exhibition information
Bole connected fuse links
Fuse bases
Fuse alarms
Fuse carriers
Combinating electric of fuse
Automobile Fuse
High voltage fuse
Customer complaints
Marketing network
Technical FAQ
Download
Recruitment information
Recruitment line
Contact
Sitemap

Copyright © Zhejiang Mingrong Electrical Protection Co., Ltd All Rights Reserved

